

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 8080 Sprayplast

Creation date: 17.04.2024, Revision: 26.02.2025, Version: 2.0

## Section 1: Identification of the substance/mixture and of the company/undertaking

---

### 1.1 Product identifier

---

**Product name**

8080 Sprayplast

**UFI:**

R29N-4C3X-M00H-NGSH



<https://my.chemius.net/p/V855CW/en/pd/en>

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

---

**Relevant identified uses**

No information.

**Uses advised against**

No information.

### 1.3 Details of the supplier of the safety data sheet

---

**Supplier**

SILCO d.o.o.  
Sentrupert 5a  
3303 Gomilsko, Slovenia  
+386 3 703 3180  
msds@silco.si

### 1.4 Emergency Telephone Number

---

**Emergency**

111

**Supplier**

112

## Section 2: Hazards identification

---

### 2.1 Classification of the substance or mixture

---

**Classification according to Regulation (EC) No 1272/2008 (CLP)**

Flam. Liq. 2; H225 Highly flammable liquid and vapour.  
Skin Irrit. 2; H315 Causes skin irritation.  
Skin Sens. 1; H317 May cause an allergic skin reaction.  
Eye Irrit. 2; H319 Causes serious eye irritation.  
Repr. 2; H361d Suspected of damaging the unborn child.

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006

***silco***<sup>®</sup>

Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

STOT RE 1; H372 Causes damage to organs (hearing organs) through prolonged or repeated exposure.

## 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP)**



**Signal word: DANGER**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs (hearing organs) through prolonged or repeated exposure.

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulation.

**Contains:**

styrene

maleic anhydride

## 2.3 Other hazards

**PBT/vPvB**

No information.

**Endocrine disrupting properties**

The product does not contain substances with the potential for endocrine disorders.

**Additional information**

No information.

## Section 3: Composition/information on ingredients

### 3.1 Substances

For mixtures see 3.2.

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

## 3.2 Mixtures

| Name  | CAS<br>EC<br>Index<br>REACH           | %            | Classification according to<br>Regulation (EC) No 1272/2008<br>(CLP)   | Specific Concentration Limits      |
|---|---------------------------------------|--------------|--|------------------------------------|
| <b>Talc</b>                                       | 14807-96-6<br>238-877-9<br>-          | 25-30        | /  | /                                  |
| <b>styrene</b>                                    | 100-42-5<br>202-851-5<br>601-026-00-0 | 15-20        | Flam. Liq. 3; H226<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>Acute Tox. 4; H332<br>Repr. 2; H361d<br>STOT RE 1; H372 (hearing<br>organs)                                   | /                                  |
| <b>ethyl<br/>acetate</b>                          | 141-78-6<br>205-500-4<br>607-022-00-5 | 5-10         | Flam. Liq. 2; H225<br>Eye Irrit. 2; H319<br>STOT SE 3; H336<br>EUH066  | /                                  |
| <b>Cobalt<br/>bis(2-ethyl<br/>hexanoate<br/>)</b> | 136-52-7<br>205-250-6<br>607-230-00-6 | 0.01-<br>0.1 | Repr. 1B; H360D  | /                                  |
| <b>maleic<br/>anhydride</b>                       | 108-31-6<br>203-571-6<br>607-096-00-9 | 0.01-<br>0.1 | Acute Tox. 4; H302<br>Skin Corr. 1B; H314<br>Skin Sens. 1A; H317<br>Eye Dam. 1; H318<br>Resp. Sens. 1; H334<br>STOT RE 1; H372<br>(respiratory system)<br>(inhalation)<br>EUH071 | Skin Sens. 1A; H317; C ≥<br>0.001% |

### Notes for substances

- D** Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3.

However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words "non-stabilised".

## Section 4: First aid measures

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

## 4.1 Description of first aid measures

---

### General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. When it is suspected, that there may still be harmful vapours/fumes present in the air, respiratory protection (mask; self contained breathing apparatus) must be used. Wash contaminated clothing with water before removing or use gloves.

### Following inhalation

Remove patient to fresh air - move out of dangerous area. In case of unconsciousness bring patient into stable side position and seek medical attention. If breathing is irregular or respiratory arrest occurs provide artificial respiration. Keep at rest in a position comfortable for breathing. Seek medical help immediately.

### Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. Consult a physician.

### Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. Seek medical help.

### Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Immediately consult a doctor. Show the physician the safety data sheet or label.

## 4.2 Most important symptoms and effects, both acute and delayed

---

### Following inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.

### Following skin contact

Itching, redness, pain. May cause sensitisation by skin contact (itching, redness, rashes).

### Following eye contact

Redness, tearing, pain.

### Following ingestion

May cause nausea/vomiting and diarrhea. May cause abdominal discomfort. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

## 4.3 Indication of any immediate medical attention and special treatment needed

---

Treat symptomatically.

## Section 5: Firefighting measures

---

### 5.1 Extinguishing media

---

#### Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 8080 Sprayplast

Creation date: 17.04.2024, Revision: 26.02.2025, Version: 2.0

## **Unsuitable extinguishing media**

Full water jet.

## **5.2 Special hazards arising from the substance or mixture**

---

### **Hazardous combustion products**

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

## **5.3 Advice for firefighters**

---

### **Protective actions**

In case of fire or heating do not breathe fumes/vapours. No action shall be taken involving any personal risk or without suitable training. Prolonged heating can cause an explosion. Vapours can form explosive mixtures with air. Cool containers at risk with water spray. If possible remove containers from endangered area.

### **Special protective equipment for fire-fighters**

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (BS EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (BS EN 137).

### **Additional information**

No information.

## **Section 6: ACCIDENTAL RELEASE MEASURES**

---

### **6.1 Personal precautions, protective equipment and emergency procedures**

---

#### **For non-emergency personnel**

##### **Protective equipment**

No information.

##### **Precautionary measures**

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

##### **Emergency procedures**

No action shall be taken involving any personal risk or without suitable training. Prevent access to unprotected personnel. Evacuate the danger zone. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing.

##### **For emergency responders**

Use personal protective equipment.

### **6.2 Environmental precautions**

---

Do not allow product to reach water/drains/sewage systems or permeable soil. In case of release into the environment, inform the relevant authorities.

### **6.3 Methods and material for containment and cleaning up**

---

#### **For containment**

Stem the spill if this does not pose risks.

#### **For cleaning up**

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Use only explosion-proof instruments and equipment. Use spark-proof tools. Prevent release into the sewer, water, basements or confined areas. Ventilate the premises. Clean contaminated area with plenty of water.

#### **Other information**

No information.

## **6.4 Reference to other sections**

---

See also sections 8 and 13.

## **Section 7: Handling and storage**

---

### **7.1 Precautions for safe handling**

---

#### **Protective measures**

##### **Measures to prevent fire**

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Vapours are heavier than air and spread along the floor. They form explosive mixtures with air.

##### **Measures to prevent aerosol and dust generation**

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

##### **Measures to protect the environment**

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

##### **Other measures**

No information.

##### **Advice on general occupational hygiene**

Use good personal hygiene practices - wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin, eyes and clothes. Remove contaminated clothes and wash them before reuse. Wear suitable protective equipment; see Section 8. Avoid exposure - obtain special instructions before using.

### **7.2 Conditions for safe storage, including any incompatibilities**

---

#### **Technical measures and storage conditions**

Keep in a cool, dry and well ventilated place. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising substances. Keep away from sources of ignition - no smoking.

#### **Packaging materials**

Store only in original container.

#### **Requirements for storage rooms and vessels**

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

#### **Storage temperature**

No information.

#### **Storage class**

No information.

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 8080 Sprayplast

Creation date: 17.04.2024, Revision: 26.02.2025, Version: 2.0

## Further information on storage conditions

No information.

## 7.3 Specific end use(s)

### Recommendations

No information.

### Industrial sector specific solutions

No information.

## Section 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure limit values

| Name                               | mg/m <sup>3</sup> | ml/m <sup>3</sup> | Short-term value<br>mg/m <sup>3</sup> | Short-term value<br>ml/m <sup>3</sup> | Remark | Biological Tolerance Values |
|------------------------------------|-------------------|-------------------|---------------------------------------|---------------------------------------|--------|-----------------------------|
| Styrene (100-42-5)                 | 430               | 100               | 1080                                  | 250                                   | /      | /                           |
| Ethyl acetate (141-78-6)           | 734               | 200               | 1468                                  | 400                                   | /      | /                           |
| Maleic anhydride (108-31-6)        | 1                 | /                 | 3                                     | /                                     | Sen    | /                           |
| Talc, respirable dust (14807-96-6) | 1                 | /                 | /                                     | /                                     | /      | /                           |

#### Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

#### DNEL/DMEL values

##### For product

No information.

##### For components

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| Name           | Type     | Exposure route | exp. frequency              | Remark | Value                   |
|----------------|----------|----------------|-----------------------------|--------|-------------------------|
| <b>Talc</b>    | Worker   | inhalation     | long term systemic effects  | /      | 2.16 mg/m <sup>3</sup>  |
| <b>Talc</b>    | Worker   | inhalation     | short term systemic effects | /      | 2.16 mg/m <sup>3</sup>  |
| <b>Talc</b>    | Worker   | inhalation     | long term local effects     | /      | 3.6 mg/m <sup>3</sup>   |
| <b>Talc</b>    | Worker   | inhalation     | short term local effects    | /      | 3.6 mg/m <sup>3</sup>   |
| <b>Talc</b>    | Worker   | dermal         | long term systemic effects  | /      | 43.2 mg/kg bw/day       |
| <b>Talc</b>    | Worker   | dermal         | long term local effects     | /      | 4.54 mg/cm <sup>2</sup> |
| <b>Talc</b>    | Consumer | inhalation     | long term systemic effects  | /      | 1.08 mg/m <sup>3</sup>  |
| <b>Talc</b>    | Consumer | inhalation     | short term systemic effects | /      | 1.08 mg/m <sup>3</sup>  |
| <b>Talc</b>    | Consumer | inhalation     | long term local effects     | /      | 1.8 mg/m <sup>3</sup>   |
| <b>Talc</b>    | Consumer | inhalation     | short term local effects    | /      | 1.8 mg/m <sup>3</sup>   |
| <b>Talc</b>    | Consumer | dermal         | long term systemic effects  | /      | 21.6 mg/kg bw/day       |
| <b>Talc</b>    | Consumer | dermal         | long term local effects     | /      | 2.27 mg/cm <sup>2</sup> |
| <b>Talc</b>    | Consumer | oral           | long term systemic effects  | /      | 160 mg/kg bw/day        |
| <b>Talc</b>    | Consumer | oral           | short term systemic effects | /      | 160 mg/kg bw/day        |
| <b>styrene</b> | Worker   | inhalation     | long term systemic effects  | /      | 85 mg/m <sup>3</sup>    |
| <b>styrene</b> | Worker   | inhalation     | short term systemic effects | /      | 289 mg/m <sup>3</sup>   |



# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| Name                 | Type     | Exposure route | exp. frequency              | Remark | Value                    |
|----------------------|----------|----------------|-----------------------------|--------|--------------------------|
| <b>styrene</b>       | Worker   | inhalation     | short term local effects    | /      | 306 mg/m <sup>3</sup>    |
| <b>styrene</b>       | Worker   | dermal         | long term systemic effects  | /      | 406 mg/kg bw/day         |
| <b>styrene</b>       | Consumer | inhalation     | long term systemic effects  | /      | 10.2 mg/m <sup>3</sup>   |
| <b>styrene</b>       | Consumer | inhalation     | short term systemic effects | /      | 174.25 mg/m <sup>3</sup> |
| <b>styrene</b>       | Consumer | inhalation     | short term local effects    | /      | 182.75 mg/m <sup>3</sup> |
| <b>styrene</b>       | Consumer | dermal         | long term systemic effects  | /      | 343 mg/kg bw/day         |
| <b>styrene</b>       | Consumer | oral           | long term systemic effects  | /      | 2.1 mg/kg bw/day         |
| <b>ethyl acetate</b> | Worker   | inhalation     | long term systemic effects  | /      | 734 mg/m <sup>3</sup>    |
| <b>ethyl acetate</b> | Worker   | inhalation     | short term systemic effects | /      | 1468 mg/m <sup>3</sup>   |
| <b>ethyl acetate</b> | Worker   | inhalation     | long term local effects     | /      | 734 mg/m <sup>3</sup>    |
| <b>ethyl acetate</b> | Worker   | inhalation     | short term local effects    | /      | 1468 mg/m <sup>3</sup>   |
| <b>ethyl acetate</b> | Worker   | dermal         | long term systemic effects  | /      | 63 mg/kg bw/day          |
| <b>ethyl acetate</b> | Consumer | inhalation     | long term systemic effects  | /      | 367 mg/m <sup>3</sup>    |
| <b>ethyl acetate</b> | Consumer | inhalation     | short term systemic effects | /      | 734 mg/m <sup>3</sup>    |
| <b>ethyl acetate</b> | Consumer | inhalation     | long term local effects     | /      | 367 mg/m <sup>3</sup>    |
| <b>ethyl acetate</b> | Consumer | inhalation     | short term local effects    | /      | 734 mg/m <sup>3</sup>    |

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| Name                                | Type     | Exposure route | exp. frequency              | Remark | Value                   |
|-------------------------------------|----------|----------------|-----------------------------|--------|-------------------------|
| <b>ethyl acetate</b>                | Consumer | dermal         | long term systemic effects  | /      | 37 mg/kg bw/day         |
| <b>ethyl acetate</b>                | Consumer | oral           | long term systemic effects  | /      | 4.5 mg/kg bw/day        |
| <b>Cobalt bis(2-ethylhexanoate)</b> | Worker   | inhalation     | long term local effects     | /      | 235.1 µg/m <sup>3</sup> |
| <b>Cobalt bis(2-ethylhexanoate)</b> | Consumer | inhalation     | long term local effects     | /      | 37 µg/m <sup>3</sup>    |
| <b>Cobalt bis(2-ethylhexanoate)</b> | Consumer | oral           | long term systemic effects  | /      | 175 µg/kg bw/day        |
| <b>maleic anhydride</b>             | Worker   | inhalation     | long term systemic effects  | /      | 0.4 mg/m <sup>3</sup>   |
| <b>maleic anhydride</b>             | Worker   | inhalation     | short term systemic effects | /      | 0.8 mg/m <sup>3</sup>   |
| <b>maleic anhydride</b>             | Worker   | inhalation     | long term local effects     | /      | 0.4 mg/m <sup>3</sup>   |
| <b>maleic anhydride</b>             | Worker   | inhalation     | short term local effects    | /      | 0.8 mg/m <sup>3</sup>   |

## PNEC values

### For product

No information.

### For components

| Name           | Exposure route                      | Remark     | Value                |
|----------------|-------------------------------------|------------|----------------------|
| <b>Talc</b>    | fresh water                         | /          | 597.97 mg/L          |
| <b>Talc</b>    | water, intermittent release         | /          | 597.97 mg/L          |
| <b>Talc</b>    | marine water                        | /          | 141.26 mg/L          |
| <b>Talc</b>    | water, marine, intermittent release | /          | 141.26 mg/L          |
| <b>Talc</b>    | fresh water sediment                | dry weight | 31.33 mg/kg          |
| <b>Talc</b>    | marine water sediment               | dry weight | 3.13 mg/kg           |
| <b>Talc</b>    | {p:47998}                           | /          | 10 mg/m <sup>3</sup> |
| <b>styrene</b> | fresh water                         | /          | 0.028 mg/L           |
| <b>styrene</b> | water, intermittent release         | /          | 0.04 mg/L            |

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| Name                                | Exposure route              | Remark     | Value       |
|-------------------------------------|-----------------------------|------------|-------------|
| <b>styrene</b>                      | marine water                | /          | 0.014 mg/L  |
| <b>styrene</b>                      | water treatment plant       | /          | 5 mg/L      |
| <b>styrene</b>                      | fresh water sediment        | dry weight | 0.614 mg/kg |
| <b>styrene</b>                      | marine water sediment       | dry weight | 0.307 mg/kg |
| <b>styrene</b>                      | soil                        | dry weight | 0.2 mg/kg   |
| <b>ethyl acetate</b>                | fresh water                 | /          | 0.24 mg/L   |
| <b>ethyl acetate</b>                | water, intermittent release | /          | 1.65 mg/L   |
| <b>ethyl acetate</b>                | marine water                | /          | 0.024 mg/L  |
| <b>ethyl acetate</b>                | water treatment plant       | /          | 650 mg/L    |
| <b>ethyl acetate</b>                | fresh water sediment        | dry weight | 1.15 mg/kg  |
| <b>ethyl acetate</b>                | marine water sediment       | dry weight | 0.115 mg/kg |
| <b>ethyl acetate</b>                | soil                        | dry weight | 0.148 mg/kg |
| <b>ethyl acetate</b>                | secondary poisoning         | food       | 0.2 g/kg    |
| <b>Cobalt bis(2-ethylhexanoate)</b> | fresh water                 | /          | 1.06 µg/L   |
| <b>Cobalt bis(2-ethylhexanoate)</b> | marine water                | /          | 2.36 µg/L   |
| <b>Cobalt bis(2-ethylhexanoate)</b> | water treatment plant       | /          | 0.37 mg/L   |
| <b>Cobalt bis(2-ethylhexanoate)</b> | fresh water sediment        | dry weight | 53.8 mg/kg  |
| <b>Cobalt bis(2-ethylhexanoate)</b> | marine water sediment       | dry weight | 69.8 mg/kg  |
| <b>Cobalt bis(2-ethylhexanoate)</b> | soil                        | dry weight | 10.9 mg/kg  |
| <b>maleic anhydride</b>             | fresh water                 | /          | 0.1 mg/L    |
| <b>maleic anhydride</b>             | water, intermittent release | /          | 0.428 mg/L  |
| <b>maleic anhydride</b>             | marine water                | /          | 0.01 mg/L   |
| <b>maleic anhydride</b>             | water treatment plant       | /          | 44.6 mg/L   |
| <b>maleic anhydride</b>             | fresh water sediment        | dry weight | 0.334 mg/kg |
| <b>maleic anhydride</b>             | marine water sediment       | dry weight | 0.033 mg/kg |
| <b>maleic anhydride</b>             | soil                        | dry weight | 0.042 mg/kg |

## 8.2 Exposure controls

**Appropriate engineering control**

**Substance/mixture related measures to prevent exposure during identified uses**

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

Use good personal hygiene practices – wash hands at breaks and when done working with material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothes. Do not eat, drink or smoke while working. Do not breathe vapours/aerosols.

#### **Structural measures to prevent exposure**

No information.

#### **Organisational measures to prevent exposure**

Remove all contaminated clothes immediately and wash them before reuse.

#### **Technical measures to prevent exposure**

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

#### **Personal protective equipment**

##### **Eye and face protection**

Safety glasses with side protection (BS EN ISO 16321-1:2022).

##### **Hand protection**

Protective gloves (EN ISO 374-1:2016). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

#### **Appropriate materials**

##### **Skin protection**

Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2022). At high risk of skin exposure chemical suits (BS EN 13034:2005+A1:2009) and boots may be required (BS EN ISO 20345:2022+A1:2024).

##### **Respiratory protection**

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard BS EN 137, BS EN 138.

##### **Thermal hazards**

No information.

#### **Environmental exposure controls**

##### **Substance/mixture related measures to prevent exposure**

No information.

##### **Instruction measures to prevent exposure**

No information.

##### **Organisational measures to prevent exposure**

No information.

##### **Technical measures to prevent exposure**

Do not allow product to reach drains, sewage systems or ground water.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

---

#### Important health, safety and environmental information

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 8080 Sprayplast

Creation date: 17.04.2024, Revision: 26.02.2025, Version: 2.0

|  |  |
|--|--|
| Physical state   | liquid   |
| Shape  | No information.  |
| Colour   | gray   |
| Odour  | characteristic   |
| Odour threshold  | No information.  |
| Melting/freezing point or softening point                | No information.  |
| Boiling point or initial boiling point and boiling range | > 77 °C  |
| Flammability   | No information.  |
| Lower and upper explosion limit                          | 1.1 – 6.1 % v/v (Styrene)                                      |
| Flash point  | 31 °C  |
| Auto-ignition temperature                                | < 460 °C   |
| Decomposition temperature                                | No information.  |
| pH   | Substance/mixture is non-soluble (in water).<br>Does not apply |
| Viscosity  | No information.  |
| Solubility   | No information.  |
| Partition coefficient n-octanol/water (log value)        | No information.  |
| Vapour pressure  | 6.7 hPa (Styrene)  |
| Density  | 1.8 kg/L   |
| Relative vapour/gas density                              | No information.  |
| Particle characteristics                                 | No information.  |

## 9.2 Other information

Information with regard to physical hazard classes

No information.

Other safety characteristics

Weight organic solvents

< 250 g/l (VOC)

## Section 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No information.

### 10.2 Chemical stability

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

Product is stable under normal conditions of use, recommended handling and storage conditions.

## 10.3 Possibility of hazardous reactions

Vapours and air can form flammable or explosive mixtures.

## 10.4 Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

## 10.5 Incompatible materials

Oxidants.

## 10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

## Section 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### (a) Acute toxicity

##### For components

| Name                                | Exposure route | Type             | Species | Time | Value           | Method   | Remark |
|-------------------------------------|----------------|------------------|---------|------|-----------------|----------|--------|
| <b>styrene</b>                      | oral           | LD <sub>50</sub> | rat     | /    | 5000 mg/kg      | /        | /      |
| <b>styrene</b>                      | dermal         | LD <sub>50</sub> | rat     | /    | > 2000 mg/kg    | OECD 402 | /      |
| <b>styrene</b>                      | inhalation     | LC <sub>50</sub> | rat     | 4 h  | 11.8 mg/l       | /        | /      |
| <b>ethyl acetate</b>                | oral           | LD <sub>50</sub> | rabbit  | /    | 4935 mg/kg      | /        | /      |
| <b>ethyl acetate</b>                | inhalation     | LC <sub>50</sub> | rat     | 4 h  | 1600 mg/l       | /        | /      |
| <b>Cobalt bis(2-ethylhexanoate)</b> | oral           | LD <sub>50</sub> | rat     | /    | 3129 mg/kg      | /        | /      |
| <b>Cobalt bis(2-ethylhexanoate)</b> | dermal         | LD <sub>50</sub> | rat     | /    | > 2000 mg/kg bw | OECD 402 | /      |
| <b>maleic anhydride</b>             | oral           | LD <sub>50</sub> | rat     | /    | 1090 mg/kg      | /        | /      |

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| Name                    | Exposure route | Type             | Species | Time | Value       | Method | Remark |
|-------------------------|----------------|------------------|---------|------|-------------|--------|--------|
| <b>maleic anhydride</b> | inhalation     | LC <sub>50</sub> | rat     | 1 h  | > 4.35 mg/l | /      | /      |
| <b>maleic anhydride</b> | oral           | LD <sub>50</sub> | rabbit  | /    | 2620 mg/kg  | /      | /      |

## Additional information

The product is not classified as acutely toxic.

## (b) Skin corrosion/irritation

### For components

| Name                                | Species | Time | result        | Method   | Remark |
|-------------------------------------|---------|------|---------------|----------|--------|
| <b>Cobalt bis(2-ethylhexanoate)</b> | /       | /    | Non-irritant. | OECD 431 | /      |
| <b>maleic anhydride</b>             | rabbit  | /    | Corrosive.    | /        | /      |

## Additional information

Causes skin and eye irritation.

## (c) Serious eye damage/irritation

### For components

| Name                                | Exposure route | Species | Time | result                | Method   | Remark |
|-------------------------------------|----------------|---------|------|-----------------------|----------|--------|
| <b>Cobalt bis(2-ethylhexanoate)</b> | /              | rabbit  | /    | moderately irritating | OECD 437 | /      |
| <b>Cobalt bis(2-ethylhexanoate)</b> | /              | rabbit  | /    | Irritating.           | OECD 405 | /      |

## (d) Respiratory or skin sensitisation

### For components

| Name                                | Exposure route | Species | Time | result                                   | Method   | Remark  |
|-------------------------------------|----------------|---------|------|--|----------|---------|
| <b>Cobalt bis(2-ethylhexanoate)</b> | dermal         | mouse   | /    | May cause sensitisation by skin contact. | OECD 429 | in vivo |
| <b>maleic anhydride</b>             | dermal         | /       | /    | Sensitizing.                             | /        | /       |

## Additional information

May cause an allergic skin reaction.

## (e) (Germ cell) mutagenicity

### For components

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| Name                                | Type                  | Species  | Time | result    | Method   | Remark |
|-------------------------------------|-----------------------|--|------|-----------|----------|--------|
| <b>Cobalt bis(2-ethylhexanoate)</b> | in-vitro mutagenicity | S. typhimurium TA 1535, TA 1537, TA 98, TA100 and TA 102 | /    | Negative. | OECD 471 | /      |
| <b>Cobalt bis(2-ethylhexanoate)</b> | in-vitro mutagenicity | mouse  | /    | Negative. | OECD 476 | /      |
| <b>maleic anhydride</b>             | in-vitro mutagenicity | /  | /    | Negative. | /        | /      |
| <b>maleic anhydride</b>             | in-vivo mutagenicity  | /  | /    | Negative. | /        | /      |

## (f) Carcinogenicity

### For components

| Name                    | Exposure route       | Type  | Species | Time | Value            | result | Method   | Remark                       |
|-------------------------|----------------------|-------|---------|------|------------------|--------|----------|------------------------------|
| <b>styrene</b>          | inhalation (vapours) | NOAEL | rat     | /    | 4.34 mg/l        | /      | OECD 453 | 5 days per week, 6 h per day |
| <b>maleic anhydride</b> | dermal               | NOEL  | rat     | /    | 100 mg/kg bw/day | /      | /        | /                            |

## (g) Reproductive toxicity

### For components

| Name           | Reproductive toxicity type | Type            | Species | Time | Value           | result | Method   | Remark              |
|----------------|----------------------------|-----------------|---------|------|-----------------|--------|----------|---------------------|
| <b>styrene</b> | Effect on fertility        | NOAEL (parents) | rat     | /    | 0.65 - 2.2 mg/L | /      | OECD 416 | Inhalation (vapour) |
| <b>styrene</b> | Effect on fertility        | NOAEL (F2)      | rat     | /    | 0.22 mg/L       | /      | OECD 416 | Inhalation (vapour) |
| <b>styrene</b> | Developmental toxicity     | NOAEL           | rat     | /    | 2.6 mg/L        | /      | /        | inhalation          |



# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| Name                                | Reproductive toxicity type | Type  | Species | Time | Value    | result            | Method               | Remark     |
|-------------------------------------|----------------------------|-------|---------|------|----------|-------------------|----------------------|------------|
| <b>styrene</b>                      | Teratogenicity             | NOAEL | rat     | /    | 2.6 mg/L | /                 | /                    | inhalation |
| <b>styrene</b>                      | Maternal toxicity          | LOAEL | rat     | /    | 1.3 mg/L | /                 | /                    | inhalation |
| <b>Cobalt bis(2-ethylhexanoate)</b> | /                          | /     | /       | /    | /        | Repr. 1B (H360Fd) | /                    | /          |
| <b>maleic anhydride</b>             | Reproductive toxicity      | NOAEL | rat     | /    | 55 mg/kg | /                 | two-generation study | /          |

## Summary of evaluation of the CMR properties

Suspected of damaging the unborn child.

### (h) STOT-single exposure

No information.

### Additional information

STOT SE (single exposure): Not classified.

### (i) STOT-repeated exposure

#### For components

| Name           | Exposure route       | Type  | Species | Time     | Exposure    | organ | Value     | result | Method   | Remarks |
|----------------|----------------------|-------|---------|----------|-------------|-------|-----------|--------|----------|---------|
| <b>styrene</b> | inhalation (vapours) | NOAEL | rat     | 13 weeks | sub-acute   | /     | 0.85 mg/L | /      | /        | 6h/4    |
| <b>styrene</b> | inhalation (vapours) | NOAEL | rat     | /        | sub-chronic | /     | mg/L      | /      | OECD 453 | 6h/4    |

### Additional information

Causes damage to organs through prolonged or repeated exposure.

### (j) Aspiration hazard

No information.

### Additional information

Aspiration hazard: Not classified.

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 8080 Sprayplast

Creation date: 17.04.2024, Revision: 26.02.2025, Version: 2.0

## Symptoms related to the physical, chemical and toxicological characteristics

No information.

## Interactive effects

No information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

The product does not contain substances with the potential for endocrine disorders.

### Other information

No information.

## Section 12: Ecological information

### 12.1 Toxicity

#### Acute (short-term) toxicity

##### For components

| Name             | Type             | Value        | Exposure time | Species   | Organism                               | Method           | Remark |
|------------------|------------------|--------------|---------------|-----------|--|------------------|--------|
| styrene          | LC <sub>50</sub> | 4.02 mg/L    | 96 h          | fish      | <i>Pimephales promelas</i>             | /                | /      |
| styrene          | EC <sub>50</sub> | 4.7 mg/L     | 48 h          | crustacea | <i>Daphnia magna</i>                   | OECD 202         | /      |
| styrene          | EC <sub>50</sub> | 4.9 mg/L     | 72 h          | algae     | <i>Pseudokirchneriella subcapitata</i> | EPA OTS 797.1050 | /      |
| styrene          | EC <sub>50</sub> | ca. 500 mg/L | 30 min        | bacteria  | /                                      | OECD 209         | /      |
| styrene          | EC <sub>10</sub> | 0.28 mg/L    | 96 h          | algae     | <i>Pseudokirchneriella subcapitata</i> | EPA OTS 797.1050 | /      |
| maleic anhydride | LC <sub>50</sub> | 75 mg/L      | 96 h          | fish      | <i>Lepomis macrochirus</i>             | /                | /      |
| maleic anhydride | LC <sub>50</sub> | 75 mg/L      | 96            | fish      | <i>Oncorhynchus mykiss</i>             | /                | /      |
| maleic anhydride | EC <sub>50</sub> | 42.81 mg/L   | 48 h          | crustacea | <i>Daphnia magna</i>                   | /                | /      |

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| Name                    | Type             | Value     | Exposure time | Species        | Organism                               | Method | Remark |
|-------------------------|------------------|-----------|---------------|----------------|--|--------|--------|
| <b>maleic anhydride</b> | EC <sub>50</sub> | 150 mg/L  | 72 h          | algae          | <i>Pseudokirchneriella subcapitata</i> | /      | /      |
| <b>maleic anhydride</b> | EC <sub>10</sub> | 44.6 mg/L | 18 h          | microorganisms | <i>Pseudomonas putida</i>              | /      | /      |

## Chronic (long-term) toxicity

### For components

| Name                    | Type | Value     | Exposure time | Species   | Organism                               | Method   | Remark |
|-------------------------|------|-----------|---------------|-----------|--|----------|--------|
| <b>styrene</b>          | NOEC | 1.01 mg/l | 21 days       | crustacea | <i>Daphnia magna</i>                   | OECD 211 | /      |
| <b>maleic anhydride</b> | NOEC | 10 mg/l   | 21 days       | crustacea | <i>Daphnia magna</i>                   | /        | /      |
| <b>maleic anhydride</b> | NOEC | 11.8 mg/l | 72 h          | algae     | <i>Pseudokirchneriella subcapitata</i> | /        | /      |

## 12.2 Persistence and degradability

### Abiotic degradation, physical- and photo-chemical elimination

No information.

### Biodegradation

#### For components

| Name                    | Type             | Rate       | Time    | Evaluation            | Method       | Remark                    |
|-------------------------|------------------|------------|---------|-----------------------|--------------|---------------------------|
| <b>Talc</b>             | Water solubility | < 0.1 mg/L | /       | /                     | /            | /                         |
| <b>styrene</b>          | biodegradability | 70.9 %     | 28 days | readily biodegradable | ISO DIN 9408 | aerobic, activated sludge |
| <b>maleic anhydride</b> | biodegradability | > 90 %     | /       | rapidly biodegradable | OECD 301 B   | /                         |

## 12.3 Bioaccumulative potential

### Partition coefficient n-octanol/water (log value)

#### For components

| Name           | Value | Temperature °C | pH | Concentration | Method |
|----------------|-------|----------------|----|---------------|--------|
| <b>styrene</b> | 2.96  | /              | /  | /             | /      |

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| Name                    | Value | Temperature °C | pH | Concentration | Method |
|-------------------------|-------|----------------|----|---------------|--------|
| <b>maleic anhydride</b> | -2.61 | /              | /  | /             | /      |

## Bioconcentration factor (BCF)

### For components

| Name           | Species | Organism | Value | Duration | Evaluation | Method | Remark           |
|----------------|---------|----------|-------|----------|------------|--------|------------------|
| <b>styrene</b> | BCF     | fish     | 13.5  | /        | /          | /      | /                |
| <b>styrene</b> | BCF     | /        | 74    | /        | /          | /      | Calculated value |

## 12.4 Mobility in soil

### Known or predicted distribution to environmental compartments

No information.

### Surface tension

No information.

### Adsorption/Desorption

#### For components

| Name                    | Type | Criterion | Value | Evaluation | Method | Remark |
|-------------------------|------|-----------|-------|------------|--------|--------|
| <b>styrene</b>          | Soil | log KOC   | 2.55  | /          | /      | /      |
| <b>styrene</b>          | Soil | /         | 352   | /          | /      | Koc    |
| <b>maleic anhydride</b> | Soil | log KOC   | 1.63  | /          | /      | /      |

## 12.5 Results of PBT and vPvB assessment

No evaluation.

## 12.6 Endocrine disrupting properties

The product does not contain substances with the potential for endocrine disorders.

## 12.7 Other adverse effects

No information.

## 12.8 Additional information

### For product

Product is not classified as hazardous for environment. Do not allow to reach ground water, water courses or sewage system.

## Section 13: Disposal considerations

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 8080 Sprayplast

Creation date: 17.04.2024, Revision: 26.02.2025, Version: 2.0

## 13.1 Waste treatment methods

### Product / Packaging disposal

#### Waste chemical

Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

#### Waste codes / waste designations according to LoW

No information.

#### Packaging

Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents. Uncleaned containers should not be perforated, cut or welded. Empty containers represent a fire hazard as they may contain flammable product residues and vapours.

#### Waste codes / waste designations according to LoW

No information.

#### Waste treatment-relevant information

No information.





#### Sewage disposal-relevant information

No information.

#### Other disposal recommendations

No information.

## Section 14: Transport information

| ADR/RID   | IMDG  | IATA  | ADN   |
|---|---|---|---|
| <b>14.1 UN number or ID number</b>  |   |   |   |
| UN 1866   | UN 1866   | UN 1866   | UN 1866   |
| <b>14.2 UN proper shipping name</b>   |   |   |   |
| RESIN SOLUTION  | RESIN SOLUTION  | RESIN SOLUTION  | RESIN SOLUTION  |
| <b>14.3 Transport hazard class(es)</b>  |   |   |   |
| 3   | 3   | 3   | 3   |
|  |  |  |  |
| <b>14.4 Packing group</b>   |   |   |   |
| III   | III   | III   | III   |

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

| ADR/RID  | IMDG   | IATA  | ADN                       |
|--|--|---|---------------------------|
| <b>14.5 Environmental hazards</b>  |  |   |                           |
| NO   | NO   | NO  | NO                        |
| <b>14.6 Special precautions for user</b>   |  |   |                           |
| Limited quantities<br>5 L<br>Packing Instructions<br>P001, IBC03, LP01, R001<br>Special packing provisions<br>PP1<br>Transport category<br>3<br>Tunnel restriction code (D/E)<br>Classification code<br>F1 | Limited quantities<br>5 L<br>EmS<br>F-E, <u>S-E</u><br>Flash point<br>31 °C  | Limited Quantity,<br>Packing Instructions<br>(Ltd Qty, Pkg Inst)<br>Y344<br>Limited Quantity,<br>Maximum Net<br>Quantity/Package (Ltd<br>Qty, Max Net Qty/Pkg)<br>10 L<br>Packing Instructions<br>(Pkg Inst)<br>355<br>Maximum Net<br>Quantity/Package (Max<br>Net Qty/Pkg)<br>25 L<br>Special provisions<br>A3 | Limited quantities<br>5 L |
| <b>14.7 Maritime transport in bulk according to IMO instruments</b>  |  |   |                           |
|  | Goods may not be carried in bulk in bulk containers, containers or vehicles. |   |                           |

## Section 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2020/878)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

#### Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

EU limit values and category: B(b) 250 g/l. VOC Content: 250 g/l

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

## **Ingredients according to Regulation (EC) No 648/2004 on detergents**

No information.

## **Special instructions**

Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

## **15.2 Chemical Safety Assessment**

---

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## **Section 16: Other information**

---

### **Indication of changes**

No information.

### **Key literature references and sources for data**

No information.

### **Abbreviations and acronyms**

ATE - Acute Toxicity Estimate  
ADR - Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
CEN - European Committee for Standardisation  
C&L - Classification and Labelling  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
CAS# - Chemical Abstracts Service number  
CMR - Carcinogen, Mutagen, or Reproductive Toxicant  
CSA - Chemical Safety Assessment  
CSR - Chemical Safety Report  
DMEL - Derived Minimal Effect Level  
DNEL - Derived No Effect Level  
DPD - Dangerous Preparations Directive 1999/45/EC  
DSD - Dangerous Substances Directive 67/548/EEC  
DU - Downstream User  
EC - European Community  
ECHA - European Chemicals Agency  
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)  
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)  
EEC - European Economic Community  
EINECS - European Inventory of Existing Commercial Substances  
ELINCS - European List of notified Chemical Substances  
EN - European Standard  
EQS - Environmental Quality Standard  
EU - European Union  
Euphrac - European Phrase Catalogue  
EWC - European Waste Catalogue (replaced by LoW - see below)  
GES - Generic Exposure Scenario  
GHS - Globally Harmonized System  
IATA - International Air Transport Association  
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG - International Maritime Dangerous Goods  
IMSBC - International Maritime Solid Bulk Cargoes

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

IT - Information Technology  
IUCLID - International Uniform Chemical Information Database  
IUPAC - International Union for Pure Applied Chemistry  
JRC - Joint Research Centre  
Kow - octanol-water partition coefficient  
LC50 - Lethal Concentration to 50 % of a test population  
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)  
LE - Legal Entity  
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)  
LR - Lead Registrant  
M/I - Manufacturer / Importer  
MS - Member States  
MSDS - Material Safety Data Sheet  
OC - Operational Conditions  
OECD - Organization for Economic Co-operation and Development  
OEL - Occupational Exposure Limit  
OJ - Official Journal  
OR - Only Representative  
OSHA - European Agency for Safety and Health at work  
PBT - Persistent, Bioaccumulative and Toxic substance  
PEC - Predicted Effect Concentration  
PNEC(s) - Predicted No Effect Concentration(s)  
PPE - Personal Protection Equipment  
(Q)SAR - Qualitative Structure Activity Relationship  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals (Regulation (EC) No 1907/2006)  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
RIP - REACH Implementation Project  
RMM - Risk Management Measure  
SCBA - Self-Contained Breathing Apparatus  
SDS - Safety data sheet  
SIEF - Substance Information Exchange Forum  
SME - Small and Medium sized Enterprises  
STOT - Specific Target Organ Toxicity  
(STOT) RE - Repeated Exposure  
(STOT) SE - Single Exposure  
SVHC - Substances of Very High Concern  
UN - United Nations  
vPvB - Very Persistent and Very Bioaccumulative

## List of relevant H phrases

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H336 May cause drowsiness or dizziness.  
H360D May damage the unborn child.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs (hearing organs) through prolonged or repeated exposure.



# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **8080 Sprayplast**

Creation date: **17.04.2024**, Revision: **26.02.2025**, Version: **2.0**

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH071 Corrosive to the respiratory tract.