

6600 SFR Air-Bond

Fast, soft, light putty - bodyfiller

Ultra fast drying putty for perfect refinish results within minutes.

silco[®]

- / Light weight 1.3kg/L
- / Dries 40% faster than other putties
- / Sanding after 12 minutes without paper clogging
- / Excellent adhesion on various substrates



6600 SFR Air-Bond

Fast, soft, light putty - bodyfiller

Drying time*

Dry to sand 20°C / 68 F	12–14 min
----------------------------	-----------

Potlife 20°C / 68 F	3–4 min
------------------------	---------

*Indicative times subject to amount of hardener/application/environment.

How to use?

Treated surface must be clean, dry, rust-free and grease-free. Optimal adhesion can be achieved on well abraded surface. Mix the putty and hardener thoroughly until the colour is even. Use filler knife, plastic or rubber spatula for the application. Do not overdose! Excessive quantity of hardener can cause colour change on the topcoat and shorten the potlife. Hardener quantities below 2% can result in prolonged drying time.

For further and updated information please refer to the TDS published on www.silco.si.

Packaging

Putty & Hardener

Prod. Nr.	Content	Color
6600-1,3	1.3 kg	White
BPO Hardener 2–3 %	50 g	Red paste

Product info

Universal fast and soft lightweight polyester putty. Thanks to its cutting edge filling material technology, the specific weight of only 1.3 kg/L enables it to fill irregularities and dents with significantly less product (by weight) in comparison with conventional putties.

It dries up to 40% faster than conventional putties.