

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.04.2023

Version number 1

Revision: 21.04.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Ceramic Guard Xtender
- **Article number:** CGX
- **UFI:** DR9A-M0M0-900D-2HYJ
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Cartec BV  
Verbreeppark 13  
NL-2731 BR Benthuizen  
The Netherlands  
safety@cartecworld.com
- **Further information obtainable from:** Product Safety Department
- **1.4 Emergency telephone number:** During normal opening times: +31 79 3410100

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1      H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2   H411 Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02   GHS08   GHS09

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
Hydrocarbons, C10-C12, isoalcanes. <2% aromatics
- **Hazard statements**  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 28.04.2023

Version number 1

Revision: 21.04.2023

**Trade name: Ceramic Guard Xtender**

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read carefully and follow all instructions.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P240 Ground and bond container and receiving equipment.  
 P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P331 Do NOT induce vomiting.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

- 2 % of the mixture consists of component(s) of unknown toxicity.  
 Contains 2 % of components with unknown hazards to the aquatic environment.

**2.3 Other hazards****Results of PBT and vPvB assessment**

- PBT:** Not applicable.  
**vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

- Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 64741-65-7 EC number: 923-037-2	Hydrocarbons, C10-C12, isoalcanes. <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411, EUH066	50 - 100%
CAS: 78-10-4 EINECS: 201-083-8 Index number: 014-005-00-0	tetraethyl silicate ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	1 - 5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	1 - 5%
CAS: 69430-37-1	dimethylsiloxaan ⚠ Flam. Liq. 2, H225; ⚠ STOT SE 2, H371; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.25 - < 1%
CAS: 134737-05-6	Siloxanes and silicones di-Me, 3-[3-[(3-cocoamidepropyl) dimethylamonio]-2-hydroxypropoxy]proyl group-terminated, acetates (salts) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 2, H411	0.25 - < 1%

- Additional information:** For the wording of the listed hazard phrases refer to section 16.

EU

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.04.2023

Version number 1

Revision: 21.04.2023

**Trade name: Ceramic Guard Xtender**

(Contd. of page 2)

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
  - **After inhalation:** Supply fresh air; consult doctor in case of complaints.
  - **After skin contact:** Generally the product does not irritate the skin.
  - **After eye contact:** Rinse opened eye for several minutes under running water.
  - **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect from heat.  
Protect against electrostatic charges.

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 28.04.2023

Version number 1

Revision: 21.04.2023

Trade name: Ceramic Guard Xtender

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
  - Protect from frost.
  - Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

<b>78-10-4 tetraethyl silicate (1 - 5%)</b>
---

IOELV   Long-term value: 44 mg/m <sup>3</sup> , 5 ppm
---

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
  - Keep away from foodstuffs, beverages and feed.
  - Wash hands before breaks and at the end of work.
- **Respiratory protection:**
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · **Eye/face protection**



Tightly sealed goggles

EU

(Contd. on page 5)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 28.04.2023

Version number 1

Revision: 21.04.2023

Trade name: Ceramic Guard Xtender

(Contd. of page 4)

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	180 °C
· Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	23 - 60 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0.768 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.

#### · 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	88.3 %
· VOC (EC)	88.34 %
· Solids content:	0.0 %
· Change in condition	
· Evaporation rate	Not determined.

#### · Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void

(Contd. on page 6)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 28.04.2023

Version number 1

Revision: 21.04.2023

Trade name: Ceramic Guard Xtender

(Contd. of page 5)

· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

#### · Endocrine disrupting properties

556-67-2	octamethylcyclotetrasiloxane	List II, III
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)

EU

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 28.04.2023

Version number 1

Revision: 21.04.2023

Trade name: Ceramic Guard Xtender

(Contd. of page 6)

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

- **12.7 Other adverse effects**

- **Remark:** Toxic for fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

HP14	Ecotoxic
------	----------

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

## SECTION 14: Transport information

- **14.1 UN number or ID number**

- **ADR, IMDG, IATA**

UN1268

- **14.2 UN proper shipping name**

- **ADR**

1268 PETROLEUM DISTILLATES, N.O.S., ENVIRONMENTALLY HAZARDOUS

- **IMDG**

PETROLEUM DISTILLATES, N.O.S., MARINE POLLUTANT

- **IATA**

PETROLEUM DISTILLATES, N.O.S.

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class**

3 (F1) Flammable liquids.

(Contd. on page 8)

## Safety data sheet

### according to 1907/2006/EC, Article 31



Printing date 28.04.2023

Version number 1

Revision: 21.04.2023

Trade name: Ceramic Guard Xtender

(Contd. of page 7)

· Label	3
· IMDG	
	
· Class	3 Flammable liquids.
· Label	3
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Hydrocarbons, C10-C12, isoalcanes. <2% aromatics
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E,S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1268 PETROLEUM DISTILLATES, N.O.S. 3, III, ENVIRONMENTALLY HAZARDOUS

EU

(Contd. on page 9)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 28.04.2023

Version number 1

Revision: 21.04.2023

Trade name: Ceramic Guard Xtender

(Contd. of page 8)

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H371 May cause damage to organs.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 2: Specific target organ toxicity (single exposure) – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2