

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 9060 X6 UHS Clear Coat

Creation date: 08.09.2021, Revision: 22.03.2024, Version: 4.0

## Section 1: Identification of the substance/mixture and of the company/undertaking

---

### 1.1 Product identifier

---

**Product name**

9060 X6 UHS Clear Coat

**Product code**

[9060]

**UFI:**

CU2T-60XA-800P-X79N



<https://my.chemius.net/p/ykQXfr/en/pd/en>

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

---

**Relevant identified uses**

No information.

**Uses advised against**

No information.

### 1.3 Details of the supplier of the safety data sheet

---

**Manufacturer**

SILCO d.o.o.  
Sentrupert 5a  
3303 Gomilsko, Slovenia  
+386 3 703 3180  
msds@silco.si

### 1.4 Emergency Telephone Number

---

**Emergency**

112

**Manufacturer**

112

## Section 2: Hazards identification

---

### 2.1 Classification of the substance or mixture

---

**Classification according to Regulation (EC) No 1272/2008 (CLP)**

Flam. Liq. 3; H226 Flammable liquid and vapour.  
STOT SE 3; H336 May cause drowsiness or dizziness.

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006

**silco**<sup>®</sup>

Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

## 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]



**Signal word: WARNING**

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains methyl 2-methylprop-2-enoate, 2-hydroxyethyl methacrylate. May produce an allergic reaction.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulation.

**Contains:**

n-butyl acetate

## 2.3 Other hazards

**PBT/vPvB**

No information.

**Endocrine disrupting properties**

The product does not contain substances with the potential for endocrine disorders.

**Additional information**

No information.

## Section 3: Composition/information on ingredients

### 3.1 Substances

For mixtures see 3.2.

### 3.2 Mixtures

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Concentration Limits
<b>n-butyl acetate</b>	123-86-4 204-658-1 607-025-00-1	20-25	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	/
<b>xylene</b>	1330-20-7 215-535-7 601-022-00-9	15-20	Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332	/
<b>heptan-2-one</b>	110-43-0 203-767-1 606-024-00-3	2.5-5	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332	/
<b>2-butoxyethyl acetate</b>	112-07-2 203-933-3 607-038-00-2	2.5-5	Acute Tox. 4; H312 Acute Tox. 4; H332	/
<b>ethyl benzene</b>	100-41-4 202-849-4 601-023-00-4	2.5-5	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373	/
<b>methyl 2-methylprop-2-enoate</b>	80-62-6 201-297-1 607-035-00-6	0.1-1	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335	/
<b>2-hydroxyethyl methacrylate</b>	868-77-9 212-782-2 607-124-00-X	0.1-1	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319	/

## Notes for substances

**C** Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.

In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

- D** Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3.

However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words "non-stabilised".

---

## Section 4: First aid measures

---

### 4.1 Description of first aid measures

---

#### General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician.

#### Following inhalation

Remove patient to fresh air - move out of dangerous area. Obtain professional medical help!

#### Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention.

#### Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

#### Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Consult a physician. Show the physician the safety data sheet or label.

### 4.2 Most important symptoms and effects, both acute and delayed

---

#### Following inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Vapours may cause drowsiness and dizziness.

#### Following skin contact

Contact with skin may cause irritation (redness, itching). May cause sensitisation by skin contact (itching, redness, rashes). Repeated exposure may cause dry skin or cracked skin.

#### Following eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

#### Following ingestion

May cause nausea/vomiting and diarrhea. May cause abdominal discomfort.

### 4.3 Indication of any immediate medical attention and special treatment needed

---

Treat symptomatically.

## Section 5: Firefighting measures

---

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

## 5.1 Extinguishing media

---

### Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

### Unsuitable extinguishing media

Full water jet.

## 5.2 Special hazards arising from the substance or mixture

---

### Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

## 5.3 Advice for firefighters

---

### Protective actions

In case of fire or heating do not breathe fumes/vapours. No action shall be taken involving any personal risk or without suitable training. Prolonged heating can cause an explosion. Vapours can form explosive mixtures with air. Cool containers at risk with water spray. If possible remove containers from endangered area.

### Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (BS EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (BS EN 137).

### Additional information

No information.

## Section 6: ACCIDENTAL RELEASE MEASURES

---

### 6.1 Personal precautions, protective equipment and emergency procedures

---

#### For non-emergency personnel

##### Protective equipment

No information.

##### Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

##### Emergency procedures

No action shall be taken involving any personal risk or without suitable training. Prevent access to unprotected personnel. Evacuate the danger zone. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing.

##### For emergency responders

Use personal protective equipment.

### 6.2 Environmental precautions

---

Do not allow product to reach water/drains/sewage systems or permeable soil. In case of release into the environment, inform the relevant authorities.

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 9060 X6 UHS Clear Coat

Creation date: 08.09.2021, Revision: 22.03.2024, Version: 4.0

## 6.3 Methods and material for containment and cleaning up

---

### For containment

Stem the spill if this does not pose risks.

### For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Use only explosion-proof instruments and equipment. Use spark-proof tools. Prevent release into the sewer, water, basements or confined areas. Ventilate the premises. Clean contaminated area with plenty of water.

### Other information

No information.

## 6.4 Reference to other sections

---

See also sections 8 and 13.

## Section 7: Handling and storage

---

### 7.1 Precautions for safe handling

---

#### Protective measures

##### Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Vapours are heavier than air and spread along the floor. They form explosive mixtures with air.

##### Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

##### Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

##### Other measures

No information.

##### Advice on general occupational hygiene

Use good personal hygiene practices - wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin, eyes and clothes. Remove contaminated clothes and wash them before reuse. Wear suitable protective equipment; see Section 8.

### 7.2 Conditions for safe storage, including any incompatibilities

---

#### Technical measures and storage conditions

Keep in a cool, dry and well ventilated place. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising substances. Keep away from sources of ignition - no smoking.

#### Packaging materials

Store only in original container.

#### Requirements for storage rooms and vessels

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

## Storage temperature

No information.

## Storage class

No information.

## Further information on storage conditions

No information.

## 7.3 Specific end use(s)

### Recommendations

No information.

### Industrial sector specific solutions

No information.

## Section 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure limit values

Name	mg/m <sup>3</sup>	ml/m <sup>3</sup>	Short-term value mg/m <sup>3</sup>	Short-term value ml/m <sup>3</sup>	Remark	Biological Tolerance Values
<b>Ethylbenzene (100-41-4)</b>	441	100	552	125	Sk	/
<b>Xylene, o-,m-,p - or mixed isomers (1330-20-7)</b>	220	50	441	100	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift
<b>2-Butoxyethyl acetate (112-07-2)</b>	133	20	332	50	Sk	/
<b>Butyl acetate (123-86-4)</b>	724	150	966	200	/	/

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

Name	mg/m <sup>3</sup>	ml/m <sup>3</sup>	Short-term value mg/m <sup>3</sup>	Short-term value ml/m <sup>3</sup>	Remark	Biological Tolerance Values
<b>Heptan-2-one (110-43-0)</b>	237	50	475	100	Sk	/
<b>Methyl methacrylate (80-62-6)</b>	208	50	416	100	/	/

### Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

### DNEL/DMEL values

#### For product

No information.

#### For components

Name	Type	Exposure route	exp. frequency	Remark	value
<b>n-butyl acetate</b>	Worker	inhalation	long term systemic effects	/	300 mg/m <sup>3</sup>
<b>n-butyl acetate</b>	Worker	inhalation	short term systemic effects	/	600 mg/m <sup>3</sup>
<b>n-butyl acetate</b>	Worker	inhalation	long term local effects	/	300 mg/m <sup>3</sup>
<b>n-butyl acetate</b>	Worker	inhalation	short term local effects	/	600 mg/m <sup>3</sup>
<b>n-butyl acetate</b>	Worker	dermal	long term systemic effects	/	11 mg/kg bw/day
<b>n-butyl acetate</b>	Worker	dermal	short term systemic effects	/	11 mg/kg bw/day
<b>n-butyl acetate</b>	Consumer	inhalation	long term systemic effects	/	35.7 mg/m <sup>3</sup>

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

Name	Type	Exposure route	exp. frequency	Remark	value
<b>n-butyl acetate</b>	Consumer	inhalation	short term systemic effects	/	300 mg/m <sup>3</sup>
<b>n-butyl acetate</b>	Consumer	inhalation	long term local effects	/	35.7 mg/m <sup>3</sup>
<b>n-butyl acetate</b>	Consumer	inhalation	short term local effects	/	300 mg/m <sup>3</sup>
<b>n-butyl acetate</b>	Consumer	dermal	long term systemic effects	/	6 mg/kg bw/day
<b>n-butyl acetate</b>	Consumer	dermal	short term systemic effects	/	6 mg/kg bw/day
<b>n-butyl acetate</b>	Consumer	oral	long term systemic effects	/	2 mg/kg bw/day
<b>n-butyl acetate</b>	Consumer	oral	short term systemic effects	/	2 mg/kg bw/day
<b>methyl 2-methylprop-2-enoate</b>	Worker	inhalation	long term systemic effects	/	208 mg/m <sup>3</sup>
<b>methyl 2-methylprop-2-enoate</b>	Worker	inhalation	long term local effects	/	208 mg/m <sup>3</sup>
<b>methyl 2-methylprop-2-enoate</b>	Worker	dermal	long term systemic effects	/	13.67 mg/kg bw/day
<b>methyl 2-methylprop-2-enoate</b>	Worker	dermal	long term local effects	/	1.5 mg/cm <sup>2</sup>
<b>methyl 2-methylprop-2-enoate</b>	Worker	dermal	short term local effects	/	1.5 mg/cm <sup>2</sup>
<b>methyl 2-methylprop-2-enoate</b>	Consumer	inhalation	long term systemic effects	/	74.3 mg/m <sup>3</sup>
<b>methyl 2-methylprop-2-enoate</b>	Consumer	inhalation	long term local effects	/	104 mg/m <sup>3</sup>
<b>methyl 2-methylprop-2-enoate</b>	Consumer	dermal	long term systemic effects	/	8.2 mg/kg bw/day

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

Name	Type	Exposure route	exp. frequency	Remark	value
<b>methyl 2-methylprop-2-enoate</b>	Consumer	dermal	long term local effects	/	1.5 mg/cm <sup>2</sup>
<b>methyl 2-methylprop-2-enoate</b>	Consumer	dermal	short term local effects	/	1.5 mg/cm <sup>2</sup>
<b>2-butoxyethyl acetate</b>	Worker	inhalation	long term systemic effects	/	133 mg/m <sup>3</sup>
<b>2-butoxyethyl acetate</b>	Worker	inhalation	short term local effects	/	333 mg/m <sup>3</sup>
<b>2-butoxyethyl acetate</b>	Worker	dermal	long term systemic effects	/	169 mg/kg bw/day
<b>2-butoxyethyl acetate</b>	Worker	dermal	short term systemic effects	/	120 mg/kg bw/day
<b>2-butoxyethyl acetate</b>	Consumer	inhalation	long term systemic effects	/	80 mg/m <sup>3</sup>
<b>2-butoxyethyl acetate</b>	Consumer	inhalation	short term local effects	/	200 mg/m <sup>3</sup>
<b>2-butoxyethyl acetate</b>	Consumer	dermal	long term systemic effects	/	102 mg/kg bw/day
<b>2-butoxyethyl acetate</b>	Consumer	dermal	short term systemic effects	/	72 mg/kg bw/day
<b>2-butoxyethyl acetate</b>	Consumer	oral	long term systemic effects	/	8.6 mg/kg bw/day
<b>2-butoxyethyl acetate</b>	Consumer	oral	short term systemic effects	/	36 mg/kg bw/day
<b>2-hydroxyethyl methacrylate</b>	Worker	dermal	long term systemic effects	mg/kg per day	1.3 mg/kg
<b>2-hydroxyethyl methacrylate</b>	Worker	inhalation	long term systemic effects	/	4.9 mg/m <sup>3</sup>
<b>2-hydroxyethyl methacrylate</b>	Consumer	dermal	long term systemic effects	mg/kg per day	0.83 mg/kg

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

Name	Type	Exposure route	exp. frequency	Remark	value
<b>2-hydroxyethyl methacrylate</b>	Consumer	inhalation	long term systemic effects	/	2.9 mg/m <sup>3</sup>
<b>2-hydroxyethyl methacrylate</b>	Consumer	oral	long term systemic effects	mg/kg per day	0.83 mg/kg

## PNEC values

### For product

No information.

### For components

Name	Exposure route	Remark	value
<b>n-butyl acetate</b>	fresh water	/	0.18 mg/L
<b>n-butyl acetate</b>	water, intermittent release	/	0.36 mg/L
<b>n-butyl acetate</b>	marine water	/	0.018 mg/L
<b>n-butyl acetate</b>	water treatment plant	/	35.6 mg/L
<b>n-butyl acetate</b>	fresh water sediment	dry weight	0.981 mg/kg
<b>n-butyl acetate</b>	marine water sediment	dry weight	0.098 mg/kg
<b>n-butyl acetate</b>	soil	dry weight	0.09 mg/kg
<b>methyl 2-methylprop-2-enoate</b>	fresh water	/	0.94 mg/L
<b>methyl 2-methylprop-2-enoate</b>	water, intermittent release	/	0.94 mg/L
<b>methyl 2-methylprop-2-enoate</b>	marine water	/	0.94 mg/L
<b>methyl 2-methylprop-2-enoate</b>	water treatment plant	/	10 mg/L
<b>methyl 2-methylprop-2-enoate</b>	fresh water sediment	dry weight	5.74 mg/kg
<b>methyl 2-methylprop-2-enoate</b>	soil	dry weight	1.47 mg/kg
<b>2-butoxyethyl acetate</b>	fresh water	/	0.304 mg/L
<b>2-butoxyethyl acetate</b>	water, intermittent release	/	0.56 mg/L
<b>2-butoxyethyl acetate</b>	marine water	/	0.03 mg/L
<b>2-butoxyethyl acetate</b>	water treatment plant	/	90 mg/L
<b>2-butoxyethyl acetate</b>	fresh water sediment	dry weight	2.03 mg/kg
<b>2-butoxyethyl acetate</b>	marine water sediment	dry weight	0.203 mg/kg
<b>2-butoxyethyl acetate</b>	soil	dry weight	0.415 mg/kg

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

Name	Exposure route	Remark	value
<b>2-butoxyethyl acetate</b>	secondary poisoning	food	60 mg/kg
<b>2-hydroxyethyl methacrylate</b>	fresh water	/	0.482 mg/L
<b>2-hydroxyethyl methacrylate</b>	marine water	/	0.482 mg/L
<b>2-hydroxyethyl methacrylate</b>	water treatment plant	/	10 mg/L
<b>2-hydroxyethyl methacrylate</b>	water, intermittent release	/	1 mg/L
<b>2-hydroxyethyl methacrylate</b>	fresh water sediment	/	3.79 mg/kg
<b>2-hydroxyethyl methacrylate</b>	marine water sediment	/	3.79 mg/kg
<b>2-hydroxyethyl methacrylate</b>	soil	/	0.476 mg/kg

## 8.2 Exposure controls

### Appropriate engineering control

#### Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothes. Do not eat, drink or smoke while working. Do not breathe vapours/aerosols.

#### Structural measures to prevent exposure

No information.

#### Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

#### Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

### Personal protective equipment

#### Eye and face protection

Safety glasses with side protection (BS EN ISO 16321-1:2022).

#### Hand protection

Protective gloves (EN ISO 374-1:2016). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

### Appropriate materials

#### Skin protection

Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). At high risk of skin exposure chemical suits (EN

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

13034:2005+A1:2009) and boots may be required (EN ISO 20345:2022).

## **Respiratory protection**

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

## **Thermal hazards**

No information.

## **Environmental exposure controls**

### **Substance/mixture related measures to prevent exposure**

No information.

### **Instruction measures to prevent exposure**

No information.

### **Organisational measures to prevent exposure**

No information.

### **Technical measures to prevent exposure**

Do not allow product to reach drains, sewage systems or ground water.

## **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

### **9.1 Information on basic physical and chemical properties**

---

#### **Important health, safety and environmental information**

<b>Physical state</b>	liquid
<b>Shape</b>	No information.
<b>Colour</b>	colourless
<b>Odour</b>	No information.
<b>Odour threshold</b>	No information.
<b>Melting/freezing point or softening point</b>	No information.
<b>Boiling point or initial boiling point and boiling range</b>	No information.
<b>Flammability (solid, gas)</b>	No information.
<b>Explosion limits (vol%)</b>	No information.
<b>Flash point</b>	24 °C
<b>Auto-ignition temperature</b>	No information.
<b>Decomposition temperature</b>	No information.
<b>pH</b>	7 at 20 °C, conc. 100
<b>Viscosity</b>	No information.
<b>Solubility</b>	No information.
<b>Partition coefficient n-octanol/water (log value)</b>	No information.
<b>Vapour pressure</b>	No information.
<b>Density</b>	0.99 – 1.05 kg/L at 20 °C

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 9060 X6 UHS Clear Coat

Creation date: 08.09.2021, Revision: 22.03.2024, Version: 4.0

<b>Relative vapour/gas density</b>	No information.
<b>Particle characteristics</b>	No information.

## 9.2 Other information

### Information with regard to physical hazard classes

No information.

### Other safety characteristics

<b>Weight organic solvents</b>	315 g/l (VOC (CH)) 420 g/l (2004/42/EC)
<b>Solids content</b>	685 %

## Section 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No information.

### 10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

### 10.3 Possibility of hazardous reactions

Vapours and air can form flammable or explosive mixtures.

### 10.4 Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

### 10.5 Incompatible materials

Oxidants.

### 10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

## Section 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### (a) Acute toxicity

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

## For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
<b>n-butyl acetate</b>	dermal	LD <sub>50</sub>	rabbit	/	5000 mg/kg	/	/
<b>n-butyl acetate</b>	inhalation	LC <sub>50</sub>	rat	4 h	9.6 - 29.2 mg/l	/	dust/aerosol
<b>n-butyl acetate</b>	oral	LD <sub>50</sub>	rat	/	4700 mg/kg	/	/
<b>methyl 2-methylprop-2-enoate</b>	oral	LD <sub>50</sub>	rat	/	7872 mg/kg	/	/
<b>methyl 2-methylprop-2-enoate</b>	dermal	LD <sub>50</sub>	rabbit	/	> 5000 mg/kg	/	/
<b>methyl 2-methylprop-2-enoate</b>	inhalation (vapours)	LC <sub>50</sub>	rat	4 h	78000 mg/m <sup>3</sup>	/	/
<b>2-butoxyethyl acetate</b>	oral	LD <sub>50</sub>	rat	/	2400 mg/kg	/	/
<b>2-butoxyethyl acetate</b>	dermal	LD <sub>50</sub>	rabbit	/	1500 mg/kg	/	/
<b>2-hydroxyethyl methacrylate</b>	oral	LD <sub>50</sub>	rat	/	5564 mg/kg	/	/
<b>2-hydroxyethyl methacrylate</b>	dermal	LD <sub>50</sub>	rabbit	/	> 3000 mg/kg	/	/

## Additional information

The product is not classified as acutely toxic.

## (b) Skin corrosion/irritation

### For components

Name	Species	Time	result	Method	Remark
<b>2-butoxyethyl acetate</b>	/	/	Prolonged and repeated contact can cause dermatitis.	/	/
<b>2-hydroxyethyl methacrylate</b>	rabbit	24 h	Irritating.	/	/

## Additional information

The product is not classified as irritating to skin and eyes.

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 9060 X6 UHS Clear Coat

Creation date: 08.09.2021, Revision: 22.03.2024, Version: 4.0

## (c) Serious eye damage/irritation

### For components

Name	Exposure route	Species	Time	result	Method	Remark
2-butoxyethyl acetate	/	/	/	Blistering on cornea.	/	/
2-butoxyethyl acetate	/	/	/	Contact with eyes causes irritation.	/	/
2-butoxyethyl acetate	/	/	/	Contact with the eyes is painful.	/	/

## (d) Respiratory or skin sensitisation

No information.

### Additional information

It contains at least one ingredient that can cause sensitisation. Can cause allergic reaction. May cause an allergic skin reaction. The product is not classified as sensitising.

## (e) (Germ cell) mutagenicity

### For components

Name	Type	Species	Time	result	Method	Remark
2-hydroxyethyl methacrylate	in-vitro mutagenicity	/	/	chromosome aberration: positive	OECD 473	/
2-hydroxyethyl methacrylate	in-vitro mutagenicity	Bacteria	/	Negative.	OECD 471 (EU B. 12/13)	/

## (f) Carcinogenicity

No information.

## (g) Reproductive toxicity

No information.

### Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

## (h) STOT-single exposure

### For components

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

Name	Exposure route	Type	Species	Time	Exposure	organ	value	result	Method	Rem
<b>2-butoxyethyl acetate</b>	inhalation	/	/	/	/	/	/	Vapours can cause headache and vomiting.	/	/
<b>2-butoxyethyl acetate</b>	inhalation	/	/	/	/	/	/	Narcosis and depression of the central nervous system, damage to the liver and kidneys.	/	/

### Additional information

May cause drowsiness or dizziness. STOT SE (single exposure): Not classified.

#### (i) STOT-repeated exposure

No information.

### Additional information

Repeated exposure may cause skin dryness or cracking. STOT RE (repeated exposure): Not classified.

#### (j) Aspiration hazard

No information.

### Additional information

Aspiration hazard: Not classified.

### Symptoms related to the physical, chemical and toxicological characteristics

No information.

### Interactive effects

No information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

The product does not contain substances with the potential for endocrine disorders.

### Other information

No information.

## Section 12: Ecological information

### 12.1 Toxicity

#### Acute (short-term) toxicity

##### For components

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

Name	Type	value	Exposure time	Species	organism	Method	Remark
<b>n-butyl acetate</b>	LC <sub>50</sub>	18 mg/L	96 h	fish	/	/	/
<b>n-butyl acetate</b>	EC <sub>50</sub>	44 mg/L	48 h	crustacea	/	/	/
<b>n-butyl acetate</b>	EC <sub>50</sub>	675 mg/L	72 h	algae	/	/	/
<b>methyl 2-methylprop-2-enoate</b>	LC <sub>50</sub>	1300 mg/L	96 h	fish	<i>Pimephales promelas</i>	/	/
<b>2-butoxyethyl acetate</b>	EC <sub>50</sub>	150 mg/L	48 h	crustacea	/	/	/
<b>2-butoxyethyl acetate</b>	EC <sub>50</sub>	500 mg/L	72 h	algae	/	/	/
<b>2-butoxyethyl acetate</b>	LC <sub>50</sub>	80 mg/L	96 h	fish	/	/	/
<b>2-butoxyethyl acetate</b>	EC <sub>50</sub>	2800 mg/L	0	bacteria	/	/	/
<b>2-hydroxyethyl methacrylate</b>	LC <sub>50</sub>	227 mg/L	96 h	fish	<i>Pimephales promelas</i>	/	/

## Chronic (long-term) toxicity

No information.

## 12.2 Persistence and degradability

### Abiotic degradation, physical- and photo-chemical elimination

No information.

### Biodegradation

#### For components

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 9060 X6 UHS Clear Coat

Creation date: 08.09.2021, Revision: 22.03.2024, Version: 4.0

Name	Type	Rate	Time	Evaluation	Method	Remark
2-hydroxyethyl methacrylate	aerobic	98 %	/	inherently biodegradable	OECD 301 E	/
2-hydroxyethyl methacrylate	aerobic	84 %	/	quickly biodegradable	Translation required (16969)	/

## 12.3 Bioaccumulative potential

### Partition coefficient n-octanol/water (log value)

For components

Name	value	Temperature °C	pH	Concentration	Method
methyl 2-methylprop-2-enoate	1.38	/	/	/	/
2-hydroxyethyl methacrylate	0.47	/	/	/	/

### Bioconcentration factor (BCF)

No information.

## 12.4 Mobility in soil

### Known or predicted distribution to environmental compartments

No information.

### Surface tension

No information.

### Adsorption/Desorption

No information.

## 12.5 Results of PBT and vPvB assessment

No evaluation.

## 12.6 Endocrine disrupting properties

The product does not contain substances with the potential for endocrine disorders.

## 12.7 Other adverse effects

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

No information.

## 12.8 Additional information

---

### For product

Product is not classified as dangerous for environment. Do not allow to reach ground water, water courses or sewage system.

## Section 13: Disposal considerations

---

### 13.1 Waste treatment methods

---

#### Product / Packaging disposal

##### Waste chemical

Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

##### Waste codes / waste designations according to LoW

No information.

##### Packaging

Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents. Uncleaned containers should not be perforated, cut or welded. Empty containers represent a fire hazard as they may contain flammable product residues and vapours.

##### Waste codes / waste designations according to LoW

No information.

##### Waste treatment-relevant information

No information.

##### Sewage disposal-relevant information

No information.

##### Other disposal recommendations

No information.

## Section 14: Transport information

---

ADR/RID	IMDG	IATA	ADN
<b>14.1 UN number or ID number</b>			
UN 1263	UN 1263	UN 1263	UN 1263
<b>14.2 UN proper shipping name</b>			
PAINT	PAINT	PAINT	PAINT
<b>14.3 Transport hazard class(es)</b>			
3	3	3	3

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

ADR/RID	IMDG	IATA	ADN
			
<b>14.4 Packing group</b>			
III	III	III	III
<b>14.5 Environmental hazards</b>			
NO	NO	NO	NO
<b>14.6 Special precautions for user</b>			
Limited quantities 5 L Special provisions 163, 367, 650 Packing Instructions P001, IBC03, LP01, R001 Special packing provisions PP1 Transport category 3 Tunnel restriction code (D/E) Classification code F1	Limited quantities 5 L EmS F-E, <u>S-E</u> Flash point 24 °C	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y344 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 10 L Packing Instructions (Pkg Inst) 355 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 L Cargo Aircraft Only, Packing Instructions (CAO, Pkg Inst) 366 Special provisions A3, A72, A192 ERG code 3L	Limited quantities 5 L
<b>14.7 Maritime transport in bulk according to IMO instruments</b>			
	Goods may not be carried in bulk in bulk containers, containers or vehicles.		

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: 9060 X6 UHS Clear Coat

Creation date: 08.09.2021, Revision: 22.03.2024, Version: 4.0

## Section 15: Regulatory information

---

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

---

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)(including last amendment Commission Regulation (EU) 2020/878)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

#### Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

EU limit values and category: B(d2) 420 g/l. VOC Content: 420 g/l

#### Ingredients according to Regulation (EC) No 648/2004 on detergents

No information.

#### Special instructions

Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

### 15.2 Chemical Safety Assessment

---

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## Section 16: Other information

---

#### Indication of changes

8.1 Control parameters 9.1 Information on basic physical and chemical properties 9.2 Other information 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 12.3 Bioaccumulative potential

#### Key literature references and sources for data

No information.

#### Abbreviations and acronyms

ATE - Acute Toxicity Estimate  
ADR - Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
CEN - European Committee for Standardisation  
C&L - Classification and Labelling  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
CAS# - Chemical Abstracts Service number  
CMR - Carcinogen, Mutagen, or Reproductive Toxicant  
CSA - Chemical Safety Assessment  
CSR - Chemical Safety Report  
DMEL - Derived Minimal Effect Level  
DNEL - Derived No Effect Level  
DPD - Dangerous Preparations Directive 1999/45/EC  
DSD - Dangerous Substances Directive 67/548/EEC

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

DU - Downstream User  
EC - European Community  
ECHA - European Chemicals Agency  
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)  
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)  
EEC - European Economic Community  
EINECS - European Inventory of Existing Commercial Substances  
ELINCS - European List of notified Chemical Substances  
EN - European Standard  
EQS - Environmental Quality Standard  
EU - European Union  
Euphrac - European Phrase Catalogue  
EWC - European Waste Catalogue (replaced by LoW - see below)  
GES - Generic Exposure Scenario  
GHS - Globally Harmonized System  
IATA - International Air Transport Association  
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG - International Maritime Dangerous Goods  
IMSBC - International Maritime Solid Bulk Cargoes  
IT - Information Technology  
IUCLID - International Uniform Chemical Information Database  
IUPAC - International Union for Pure Applied Chemistry  
JRC - Joint Research Centre  
Kow - octanol-water partition coefficient  
LC50 - Lethal Concentration to 50 % of a test population  
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)  
LE - Legal Entity  
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)  
LR - Lead Registrant  
M/I - Manufacturer / Importer  
MS - Member States  
MSDS - Material Safety Data Sheet  
OC - Operational Conditions  
OECD - Organization for Economic Co-operation and Development  
OEL - Occupational Exposure Limit  
OJ - Official Journal  
OR - Only Representative  
OSHA - European Agency for Safety and Health at work  
PBT - Persistent, Bioaccumulative and Toxic substance  
PEC - Predicted Effect Concentration  
PNEC(s) - Predicted No Effect Concentration(s)  
PPE - Personal Protection Equipment  
(Q)SAR - Qualitative Structure Activity Relationship  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
RIP - REACH Implementation Project  
RMM - Risk Management Measure  
SCBA - Self-Contained Breathing Apparatus  
SDS - Safety data sheet  
SIEF - Substance Information Exchange Forum  
SME - Small and Medium sized Enterprises  
STOT - Specific Target Organ Toxicity  
(STOT) RE - Repeated Exposure

# SAFETY DATA SHEET

ACCORDING TO REGULATION (EC) 1907/2006



Product name: **9060 X6 UHS Clear Coat**

Creation date: **08.09.2021**, Revision: **22.03.2024**, Version: **4.0**

(STOT)SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

## **List of relevant H phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.