

3015 Cavity Wax

silco[®]

Cavity protection

A high-performance wax-based coating that provides strong anti-corrosion protection for vehicle cavities. It offers excellent adhesion, water repellence, and deep penetration to guard against rust and moisture.

- / Extends the lifespan of metal surfaces
- / Reaches and protects hard-to-access areas
- / Safe for plastics, rubbers, and paints
- / Shields against salt, moisture, and corrosion
- / Continuous protection without reapplication

www.silco.si



3015 Cavity Wax

Cavity protection

Product info

3015 Cavity Wax is a high-performance, wax-based protective coating designed to provide exceptional anti-corrosion protection for vehicle body cavities.

Available in 1 L bottle for application with an underbody texture gun (2006 UBS Gun), it offers excellent adhesion, water repellence, and weather resistance. Its high penetration ability ensures thorough coverage, remaining flexible after application to offer ongoing protection against rust, moisture, and road salt in vulnerable areas like door pillars, sills, and engine compartments.

Technical information

Base	Modified Petrolatum, Sulfonates, oil, solvents and additives
Colour	Transparent
Coverage	5 m ² per 1 liter
Drying time (20°C)	2 h (dust dry)
Recommended layer thickness	200 µm wet 100 µm dry
Operating temperature	-30–80 °C
Application temperature	10–25°C

How to use?

1. Use on room temperature.
2. Shake the can well before use.
3. Surface must be dry and clean, free from dirt, rust, grease etc.
4. Spray an even layer on the object or surface to be coated.
5. **Leave to evaporate/dry.**
6. Do not spray on the exhaust, brake systems, or on motor parts.

Packaging

Cartridge	1 L
Per box	12 pcs